

# EPS-1132

## 32-CH Sinking Type Digital Input Module



### Features

- 32-CH sinking type digital input
- Quick removable European type connector
- Slave module healthy monitoring
- Wide operation temperature range: -20°C - 60°C
- Compact size: 100 (L) x 100 (H) mm
- IEC-61131 compliant

### Ordering Information

- **EPS-1132**  
32-CH Sinking Type Digital Input Module

### Specifications

■ Power Consumption	2.76W
■ Hot Swap	Yes
■ Operating Temp.	-20-60 °C
■ Digital Input /Output Channel	32
■ Input /Output Type	Sinking
■ Input Current	IEC-61131-2 Type 1/3
■ Input Current Limit	2.3mA
■ Response Time	< 1ms
■ Self-Diagnostic	Power Communication / WDT
■ Connector Type	Phoenix Contact DFMC

# EPS-2032

## 32-CH Sourcing Type Digital Output Module



### Features

- 32-CH sourcing type digital output
- Quick removable European type connector
- Slave module healthy monitoring
- Wide operation temperature range: -20°C - 60°C
- Compact size: 100 (L) x 100 (H) mm
- IEC-61131 compliant

### Ordering Information

- **EPS-2032**  
32-CH Sourcing Type Digital Output Module

### Specifications

■ Power Consumption	2.76W
■ Hot Swap	Yes
■ Operating Temp.	-20-60 °C
■ Digital Output Channel	32
■ Output Type	Sourcing
■ Output Current (Single Node)	300mA
■ Output Current (Full node)	1.6A for 8-CH
■ Response Time	4KHz
■ Self-Diagnostic	Power / Communication / WDT
■ Connector Type	Phoenix Contact DFMC